

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A high-frequency receiving unit comprising:
 - a casing configured to incorporate a high-frequency circuit which receives a high-frequency signal and a signal processing circuit which obtains at least one of a picture signal and a data signal from the received high-frequency signal;
 - a display disposed in an opening of the casing and configured to display an output of the signal processing circuit; and
 - an antenna configured to receive the high-frequency signal and to supply it to the high-frequency circuit,wherein, when the display is viewed from the front at an angle perpendicular thereto, the antenna is disposed in any one of a top surface, a bottom surface, a right side surface, a left side surface and a back surface of the casing and located on the back side of an intermediate position for dividing the casing into two portions in a direction of depth.
2. (Currently Amended) A high-frequency receiving unit comprising:
 - a casing configured to incorporate a high-frequency circuit which receives a high-frequency signal and a signal processing circuit which obtains at least one of a picture signal and a data signal from the received high-frequency signal;
 - a display disposed in an opening of the casing and configured to display an output of the signal processing circuit; and
 - a plurality of antennas configured to receive the high-frequency signal and to supply it to the high-frequency circuit,wherein, when the display is viewed from the front at an angle perpendicular thereto, said plurality of antennas are disposed in any one of a top surface, a bottom surface, a right side surface, a left side surface and a back surface of the casing and located on the back side of an intermediate position for dividing the casing into two portions in a direction of depth.

3. (Original) A high-frequency receiving unit according to claim 2, wherein said plurality of antennas are disposed in a plurality of surfaces of the top surface, the bottom surface, the right side surface, the left side surface and the back surface of the back side of the casing.

4. (Original) A high-frequency receiving unit according to claim 2, wherein at least one of said plurality of antennas is disposed on the right side of an intermediate position for dividing the back portion of the casing into left and right portions and at least one of said plurality of antennas is disposed on the left side of the intermediate position.

5. (Currently Amended) A high-frequency receiving unit ~~according to claim 2,~~
~~wherein at least one of said plurality of antennas is disposed at a distance of one quarter~~
~~wavelength or more of the received signal separate from at least one other antenna~~
comprising:

a casing configured to incorporate a high-frequency circuit which receives a high-frequency signal and a signal processing circuit which obtains at least one of a picture signal and a data signal from the received high-frequency signal;

a display disposed in an opening of the casing and configured to display an output of the signal processing circuit; and

a plurality of antennas configured to receive the high-frequency signal and to supply it to the high-frequency circuit,

wherein, when the display is viewed from the front at an angle perpendicular thereto, said plurality of antennas are disposed in any one of a top surface, a bottom surface, a right side surface, a left side surface and a back surface of the casing and located on the back side of an intermediate position for dividing the casing into two portions in a direction of depth, and wherein at least one of the plurality of antennas is disposed at a separate position from at least another antenna in a distance of one quarter wavelength of the received signal or more.

6. (Original) A high-frequency receiving unit according to claim 2, wherein at least one of said plurality of antennas is disposed at a distance of 30 mm or more separate from at least one other antenna.

7. (Original) A high-frequency receiving unit according to claim 2, wherein the casing is constituted of a casing body configured to incorporate the signal processing circuit and a display casing configured to incorporate the display and to have a function that it can move with respect to the case body.

8. (Original) A high-frequency receiving unit according to claim 2, wherein the antenna is built in the casing.

9. (Original) A high-frequency receiving unit according to claim 8, wherein the case is raised in a portion in which the antenna is built.

10. (Original) A high-frequency receiving unit according to claim 8, wherein the portion of the casing in which the antenna is built has a marking to show the existence of the antenna.

11. (Original) A high-frequency receiving unit according to claim 2, wherein the antenna is mounted on the outside of the casing.

12. (Original) A high-frequency receiving unit according to claim 2, wherein at least one of the antennas is configured to able to move and has a function of varying an orientation of a radiant surface of the antenna or a distance between the antennas.

13. (Original) A high-frequency receiving unit according to claim 2, wherein either of a microstrip line placed on a flexible board and a coplanar line placed on a flexible board is used for connecting the antennas to the high-frequency circuit.

14. (Original) A high-frequency receiving unit according to claim 2, wherein the antenna is constituted of any one of a plane antenna, a helical antenna, and an antenna for circularly polarized waves.

15. (Canceled).

16. (New) A high-frequency receiving unit according to claim 1, wherein the casing comprises:

a main body casing section configured to incorporate a signal processing circuit for obtaining at least one of an image signal and a data signal from high-frequency signals received at the high-frequency circuit; and

a display casing section having an aperture in which the display is provided, and being movably attached to the main body casing section,

wherein, when the display is viewed from the front at an angle perpendicular thereto, said plurality of antennas are disposed in any one of a top surface, a bottom surface, a right side surface, a left side surface and a back surface of the casing and located on the back side of an intermediate position for dividing the casing into two portions in a direction of depth.

17. (New) A high-frequency receiving unit according to claim 2, wherein said plurality of antennas are provided such that their radiant surfaces face different directions.